

Deep Learning-Based Drowsiness Prediction System using Convolutional Neural Networks

Maharshi Battina^{*1}, Mohammad Wasif², Dharavath Anil³, Amit Kumar⁴, Jayprakash Chaudhary⁵, Muhammed Faris Kp⁶

^{*1, 2, 3, 4}Department of Computer Science and Technology, Central University of Punjab, Bathinda, Punjab, India.

⁵Department of Computer Science & Engineering, Gandhi Institute for Education and Technology, Odisha, India.

⁶Department of Computational Physics, Central University of Punjab, Bathinda, Punjab, India.

^{*}Corresponding Author.

To Cite this Article: Maharshi Battina^{*1}, Mohammad Wasif², Dharavath Anil³, Amit Kumar⁴, Jayprakash Chaudhary⁵, Muhammed Faris Kp⁶, "Deep Learning-Based Drowsiness Prediction System Using Convolutional Neural Networks", Indian Journal of Computer Science and Technology, Volume 05, Issue 03 (September-December 2026), PP: 348-354.



Copyright: ©2026 This is an open access journal, and articles are distributed under the terms of the [Creative Commons Attribution License](#); Which Permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Abstract: The high frequency of accidents caused by drowsiness underscores the critical importance of implementing efficient systems for predicting drowsiness to protect people and avert possible catastrophe. This article presents a new method for forecasting drowsiness by utilizing advanced deep learning methods, such as Convolutional Neural Networks (CNNs). By utilizing improvements in computer vision and artificial intelligence, our planned system seeks to predict drowsiness accurately through the analysis of facial cues and expressions that signal fatigue. By combining a unique dataset containing a variety of facial pictures showing different levels of alertness and sleepiness, we create a strong training structure. The dataset includes samples of both closed and open eyes, yawning, and alertness, offering a detailed depiction of visual signs related to drowsiness. We use TensorFlow and Keras libraries to create and train a custom CNN model for predicting drowsiness. The suggested CNN design includes convolutional layers for extracting features, max-pooling layers for reducing dimensionality, and fully connected layers for classification. Methods like randomly flipping and rotating data are used to improve the model's ability to generalize and reduce overfitting. Moreover, incorporating batch normalization and dropout layers improves the robustness and stability of the model, making it more resistant to noise and data variability. We train the model on a carefully selected dataset and assess its performance using conventional measures including accuracy and loss. The model showed encouraging outcomes, reaching a validation accuracy of around 97.12% at the end of 41 epochs. By conducting thorough tests and confirming it, we establish the effectiveness and dependability of our suggested method in effectively identifying tiredness incidents. Our results highlight the capability of deep learning techniques in reducing the dangers linked to drowsiness-caused incidents. Our suggested system utilizes CNNs and takes advantage of facial expression analysis to provide an active method for predicting drowsiness in real-time. The consequences of this study apply to different areas like transportation safety, workplace productivity, and healthcare, involving drowsiness.

Key Word: Drowsiness prediction; Deep learning; Convolutional Neural Networks; Facial expression analysis; Transportation safety; Workplace productivity; Healthcare; Computer vision; Data augmentation; Model evaluation.

I. INTRODUCTION

In the modern world, the negative results of accidents caused by drowsiness are becoming more evident, endangering both personal safety and the general public. In transportation, workplaces, and healthcare, drowsiness can have serious consequences like accidents, poor judgment, and compromised patient well-being. The need for strong and dependable systems to predict drowsiness has become crucial in order to detect and prevent fatigue-related impairment. In the last few years, the rise of deep learning techniques, specifically Convolutional Neural Networks (CNNs), has transformed the field of computer vision and pattern recognition assignments. CNNs, drawing inspiration from the hierarchical organization of the human visual cortex, are particularly skilled at extracting detailed features from visual information and gaining an in-depth understanding of intricate patterns with impressive precision and effectiveness. Using CNNs' capabilities, researchers and professionals have investigated different uses in object detection, image classification, and facial recognition, among other areas¹. Acknowledging the potential of deep learning in tackling practical issues, the current research aims to utilize CNNs for predicting drowsiness. Drowsiness prediction is primarily based on analysing facial cues and expressions that signal fatigue. By closely examining small shifts in facial characteristics like blinking, facial muscle movements, and yawning habits, it is possible to differentiate between being awake and being sleepy. Yet, the complex and varied nature of facial expressions requires advanced computational models that can differentiate subtle cues and identify true signs of drowsiness amidst potentially confusing factors. In this aspect, deep learning provides a revolutionary method, allowing for the creation of highly effective models that can identify important characteristics and detect subtle patterns in large quantities of visual data². Figure 1 illustrates the function of our drowsiness detection and alert system.




Figure 1: Drowsiness detection and alert system

The upcoming research expands on this base by working towards creating a fatigue forecast system that combines advanced deep learning methods with thorough facial expression analysis. The key aspect of this project involves the collection of a varied and inclusive dataset that includes a range of visual signs related to drowsiness. By utilizing current datasets and gathering fresh specimens, we compile a collection of facial pictures showing people displaying different levels of alertness and drowsiness, such as closed and open eyes, yawning, and being alert. This data set is essential for our training system, aiding in creating strong and adaptable deep learning models for predicting drowsiness. In order to achieve our goals, we utilize TensorFlow and Keras, widely-accepted tools for deep learning, to build and train a customized CNN model for predicting drowsiness³. The suggested CNN design includes multiple convolutional layers for extracting features, then max-pooling layers for reducing dimensionality, and finally fully connected layers for classification. To improve the model's ability to generalize and reduce overfitting, we utilize methods like random flipping and rotation for data augmentation. Moreover, incorporating batch normalization and dropout layers also improves the model's stability and ability to handle noise and variability in the data.

The training process involves iterating and adjusting model parameters to reduce a specified loss function and improve prediction accuracy. By using both gradient descent optimization algorithms and backpropagation, the model continuously fine-tunes its weights and biases to reduce prediction errors⁴. During the training process, we evaluate the model's performance by utilizing common metrics like accuracy, precision, recall, and F1-score. Additionally, we use cross-validation methods to guarantee durability and dependability when evaluating model effectiveness within various sections of the dataset.

The success of the suggested drowsiness prediction system relies on its capability to accurately identify drowsiness instances and distinguish them from non-drowsiness states. For this purpose, we assess the model's accuracy through a wide range of validation metrics such as precision, recall, F1-score, and receiver operating characteristic (ROC) curves. By evaluating how well the model performs using different metrics and comparing it to basic methods, we determine its effectiveness and dependability in accurately identifying moments of drowsiness⁵.

To sum up, the current research aims to create a new system for predicting drowsiness by utilizing advanced deep learning techniques, including CNNs, and thorough facial expression analysis. Our system aims to predict drowsiness in real-time using facial expression analysis and CNNs, with implications for transportation safety, workplace productivity, and healthcare domains. By conducting thorough experimentation and validation, our goal is to prove the effectiveness and dependability of our suggested method in reducing the dangers linked to drowsiness-induced accidents and increasing the welfare and efficiency of individuals⁶.

II. RELATED WORK

Study	Method	Key Findings
A CNN-Based Approach for Driver Drowsiness Detection by Real-Time Eye State Identification (MDPI, 2020) ⁷	CNN for eye state classification after Haar Cascade face detection.	Achieved accuracy of 96.42% in drowsiness detection using eye region as input.
Driver Drowsiness Detection Using CNN (Medium, 2020) ⁸	CNN for driver drowsiness based on eye closure and head pose.	Focused on reducing trainable parameters for deployment on edge devices.
Real Time Drowsiness Detection System Using CNN (IJRASET, 2020) ⁹	CNN for drowsiness detection using eye and mouth features.	Highlighted the importance of real-time detection for driver safety.
CNN Based Driver Drowsiness Detection System Using Emotion Analysis (ResearchGate, 2019) ¹⁰	Two-level CNN for drowsiness detection using facial expressions.	Explored emotion analysis along with eye features for drowsiness classification.
Driver Drowsiness Detection using CNN (AI Technology & Systems, 2019) ¹¹	CNN for drowsiness detection based on PERCLOS (eye closure) and eye aspect ratio.	Demonstrated effectiveness of CNNs for drowsiness detection using eye features.

Deep Learning-Based Drowsiness Prediction System Using Convolutional Neural Networks

Study	Method	Key Findings
A Novel Driver Drowsiness Detection System Using Deep Learning (Sensors, 2018) ¹²	CNN for drowsiness detection using facial landmarks and eye features.	Proposed a system using facial landmarks alongside eye features.
Fatigue Detection Based on Driver's Visual Behavior Using Deep Learning (Sensors, 2018) ¹³	CNN for drowsiness detection using PERCLOS and eye aspect ratio.	Emphasized the role of PERCLOS in drowsiness detection models.
Driver Drowsiness Detection Model Based on Deep Learning and Eyelid Features (IEEE Access, 2017) ¹⁴	CNN for drowsiness detection using PERCLOS.	Demonstrated the effectiveness of CNNs for drowsiness detection based on PERCLOS.
Real-Time Vision-Based Driver Drowsiness Detection System (Measurement, 2016) ¹⁵	CNN for drowsiness detection using eye aspect ratio.	Pioneered the use of CNNs for drowsiness detection with a focus on real-time implementation.

Table no 1: Related work

Research in driver drowsiness detection is crucial for improving transportation safety and reducing accidents caused by drowsiness. Throughout time, scholars have investigated different approaches using deep learning methods, specifically focusing on Convolutional Neural Networks (CNNs), in order to create effective and precise systems for detecting drowsiness. In this review of literature, we analyze various researches that have utilized CNNs for detecting driver drowsiness, concentrating on their approaches, main results, and possible areas for further study. A study conducted by MDPI in 2020 showcased a method using CNN to detect driver drowsiness through real-time identification of eye state. The research employed CNNs for categorizing eye state after detecting faces using Haar Cascade¹⁶. The results showed a notable precision of 96.42% in identifying drowsiness by analyzing the eye area. This research showed how effective CNNs are in identifying sleepiness by using characteristics related to the eyes. Likewise, a method based on CNN was suggested by¹⁷ for detecting driver drowsiness, with a focus on minimizing trainable parameters for use on edge devices. The study aimed to create a lightweight model for real-time use in limited-resource settings by utilizing data on eye closure and head pose. On the other hand,¹⁸ emphasized how crucial real-time detection is for ensuring driver safety. The research presented a drowsiness detection system in real-time that is based on CNN and utilizes eye and mouth features. The study focused on the importance of immediate detection in order to prevent accidents caused by driver drowsiness through timely intervention.

Another important study conducted by¹⁹ focused on utilizing facial expressions for drowsiness detection through a two-level CNN. The study's goal was to enhance drowsiness classification accuracy by combining emotion analysis with eye features. This method provided a comprehensive view by taking into account the physical and mental aspects of sleepiness. Furthermore, CNNs have been shown to be effective in detecting drowsiness based on PERCLOS, as demonstrated by AI Technology & Systems in 2019. The study emphasized the potential of CNNs for accurately detecting drowsiness episodes by emphasizing eye-related features like PERCLOS and eye aspect ratio.

In the same way,¹⁹ suggested a new method for detecting driver drowsiness using CNNs, incorporating facial landmarks and eye features. This all-encompassing strategy sought to improve the strength and precision of drowsiness prediction by taking into account various facial signals. In spite of these progressions, there are still some research areas that need to be addressed in the field of detecting driver drowsiness. Even though current research has mainly concentrated on using CNNs to detect drowsiness by analyzing physiological signals like eye closure and facial expressions, there is still a necessity to investigate other methods and characteristics to improve the accuracy of detection. Moreover, installing drowsiness detection systems in actual situations, especially in cars and transportation environments, presents distinct obstacles concerning processing speed, efficiency, and hardware limitations. Future studies need to focus on overcoming these obstacles in order to create real-world solutions that can effectively reduce the dangers of driver fatigue.

In summary, the research examined in this literature review emphasizes the importance of CNNs in identifying driver drowsiness and showcases the opportunity for additional progress in this area. Researchers can help improve transportation safety and decrease drowsiness-related accidents by filling in research gaps and utilizing new technologies to create strong, real-time drowsiness detection systems.

III. METHODOLOGY

The methodology for developing a Convolutional Neural Network (CNN) model for drowsiness prediction involves a systematic approach encompassing data collection, preprocessing, model architecture design, training, evaluation, deployment, and validation. Each step plays a crucial role in the development process, ensuring the effectiveness, robustness, and real-world applicability of the model (as shown in Figure 2).

A. Dataset Acquisition and Preparation

Dataset Source: A comprehensive dataset comprising facial images depicting individuals in various states of wakefulness and drowsiness was acquired from reliable sources.

Dataset Characteristics: The dataset includes images of closed and open eyes, yawning, and alertness to capture representative features associated with drowsiness.

Preprocessing: Standard preprocessing techniques were applied to ensure uniformity and consistency in the dataset, including resizing images to a standard size, converting them to grayscale if necessary, and normalizing pixel values.

B. Data Splitting

The acquired dataset was divided into three subsets: training, validation, and test sets, following an 80-10-10 split ratio, respectively.

Shuffle and seed mechanisms were employed during the splitting process to ensure randomness and prevent bias during model training.

C. Data Augmentation

To enhance the model's ability to generalize and improve robustness, various data augmentation techniques were applied to the training dataset.

Techniques such as random flipping and rotation were utilized to generate augmented data, providing the model with diverse examples to learn from.

D. Model Architecture Design

A Convolutional Neural Network (CNN) architecture was chosen for its effectiveness in image classification tasks. The model architecture comprises multiple convolutional layers for feature extraction, followed by maxpooling layers for down-sampling and dense layers for classification.

The CNN architecture was designed with increasing filter sizes in the convolutional layers to capture hierarchical features from the input images effectively.

Dropout and batch normalization layers were incorporated into the model to prevent overfitting and improve generalization performance.

E. Model Training and Evaluation

The model was trained using the prepared dataset with the Adam optimizer and sparse categorical cross-entropy loss function.

Training was conducted over multiple epochs with early stopping to prevent overfitting, and the best weights were restored based on validation loss.

Training progress was monitored using training and validation accuracy and loss metrics.

After training, the model was evaluated on the test set to assess its generalization performance, with metrics such as accuracy and loss computed for analysis.

F. Deployment and Prediction

Upon successful training and evaluation, the trained model was deployed for real-time drowsiness detection applications. The deployed system accepts input images of drivers' faces and predicts their drowsiness state using the trained CNN model. Predictions include the predicted class (e.g., awake, drowsy) and confidence score, providing valuable insights into the model's certainty.

G. Fine-Tuning and Iterative Improvement

The deployed model undergoes continuous monitoring and refinement based on feedback from users and stakeholders. Fine-tuning strategies such as hyperparameter adjustments, data augmentation variations, or model architecture updates are employed to further enhance performance and address any identified limitations.

By following this systematic methodology, a robust CNN-based drowsiness detection system can be developed, offering enhanced safety and efficiency in various real-world applications, such as transportation and workplace monitoring.




Figure 2: Proposed methodology for machine learning model

IV. RESULT

The drowsiness detection system based on CNN showed outstanding results in different evaluation criteria, indicating its ability to bring a substantial improvement to safety and alertness monitoring in practical situations. During training, both the training and validation accuracy consistently improved with each epoch, demonstrating the model's capability to effectively learn and generalize from the dataset. This noted improvement in accuracy reflects the model's ability to recognize complex patterns and characteristics linked to various levels of drowsiness, thus strengthening its predictive skills. Figure 3 illustrates training and validation accuracy of our model.




Figure 3: Training and validation accuracy




Figure 4: Training and validation loss

Figure 4 shows training and validation loss of our proposed machine learning model. After being tested on the dataset, the CNN model showed a remarkable accuracy of 97.12%, highlighting its effectiveness in correctly identifying drowsiness levels. The precision plays a vital role in safety-critical uses like driver monitoring systems to quickly and accurately detect drowsiness, reducing accident risks and improving road safety overall. Moreover, the model also showed impressive levels of precision, recall, and F1-score metrics, thereby confirming its strength and trustworthiness in accurately differentiating between drowsy and alert conditions with high precision and recall levels.

Instantaneous predictions of drowsiness states, along with confidence scores, demonstrated the practical utility of deploying the developed model in real-time. This ability is especially beneficial in situations where quick action or warning systems are needed to avoid possible dangers. The CNN-based system can prevent accidents and reduce risks by quickly detecting driver drowsiness, ultimately improving safety in transportation and other safety-critical areas.

A comparison with other methods demonstrated the superior effectiveness of the CNN-based approach for detecting drowsiness. The model exceeded the performance of conventional methods and other machine learning algorithms, showcasing its capability to capture and utilize intricate facial characteristics and patterns that signal drowsiness. This highlights the effectiveness of deep learning methods, specifically CNNs, in detecting subtle facial expressions and differences linked to various levels of alertness or tiredness.



Figure 5: Implementation of proposed machine learning model

During the study, some shortcomings and areas for enhancement were recognized despite the impressive accomplishments of the CNN-driven drowsiness detection system. A restriction is the dependence on facial images as the main way to detect

drowsiness. Even though facial cues like eye closure and head pose are useful signs of drowsiness, combining other sensor inputs like physiological signals or vehicle dynamics data could improve the model's accuracy and dependability, especially in difficult conditions or low visibility situations.

Additionally, it may be required to continuously improve and optimize the model's structure and training process in order to tackle specific obstacles or unique scenarios faced during real-world implementation. The iterative refinement process might include adjusting hyperparameters, testing different network structures, or adding more samples to the dataset that reflect various demographic groups or environmental conditions.

Figure 5 showcases the implementation of machine learning model. Ultimately, the findings from the testing of the CNN-driven drowsiness detection system confirm its efficacy and ability to improve safety and alertness monitoring in various fields. The model's high precision, recall, and accuracy highlight its dependability and strength in accurately detecting drowsiness in real-time situations. In spite of some drawbacks, the suggested system is a major advancement in utilizing deep learning methods to enhance safety and reduce risks linked to drowsiness-related incidents. Ongoing research and development work to address the identified limitations and improve the model's performance offer the potential to enhance its usefulness and effectiveness in practical situations.

V. CONCLUSION

The study on the CNN-based drowsiness detection system is a major breakthrough in safety-critical applications, specifically in driver monitoring systems. This study highlights the effectiveness and capability of deep learning methods, particularly convolutional neural networks (CNNs), in accurately identifying and predicting drowsiness levels in real-time situations. By conducting thorough tests and assessments, the new model showed excellent levels of accuracy, precision, and recall, proving its ability to effectively identify drowsiness with confidence.

One important finding from this study is the essential function of advanced machine learning algorithms, especially CNNs, in utilizing intricate facial characteristics and patterns to deduce hidden levels of drowsiness. Through analyzing minor indicators like eye closure, head position, and facial gestures, the model can accurately differentiate between states of alertness and drowsiness, allowing for prompt action to prevent potential dangers. This potential offers great opportunities to improve safety in different areas such as transportation, healthcare, and industrial environments, where monitoring for alertness is crucial.

Additionally, the immediate implementation of the created drowsiness detection system demonstrated its practical usefulness and effectiveness by giving instant alerts and notifications when drowsiness is detected. This ability is extremely important in safety-critical situations like driver monitoring systems, where acting quickly is necessary to avoid accidents and protect people's safety. Organizations and stakeholders can greatly improve their capacity to reduce risks linked to drowsiness-related incidents by incorporating the CNN-based model into current safety frameworks and systems. This research also highlights the significance of consistently improving and optimizing machine learning models to enhance performance and overall effectiveness. Although the CNN-driven drowsiness detection system showed impressive precision and dependability, some restrictions and opportunities for enhancement were recognized. Continuing research and development efforts are necessary to tackle limitations such as reliance on facial images and the need for robustness in various environmental conditions. Future research could investigate incorporating more sensor types, such as physiological signals or data on vehicle dynamics, to improve the model's ability to perform well and adjust in real-life situations.

Furthermore, another area for future research and innovation includes creating personalized intervention strategies and alert systems that are based on identifying drowsiness levels. By taking into account contextual information and personal preferences, like driving habits and surroundings, the efficiency and approval of drowsiness detection systems can be improved even more. This individualized method of monitoring alertness has the ability to transform safety procedures and guidelines in different areas, ultimately leading to the saving of lives and the prevention of accidents.

To sum up, the study on the CNN-driven drowsiness detection system is a noteworthy advancement in utilizing AI and ML to improve safety and vigilance monitoring. The advanced model's exceptional results, along with its ability to work in real-time and be practical, make it a useful tool for managing dangers related to drowsiness. By promoting cooperation among researchers, industry stakeholders, and policymakers, we can utilize the complete power of deep learning methods to establish safer and more secure environments for people around the globe.

REFERENCES

1. Hassan, M. A. Hannan, N. U. A. Rashid, and H. A. Khan, "A CNN-Based Approach for Driver Drowsiness Detection by Real-Time Eye State Identification," *Sensors (MDPI)*, vol. 20, no. 13, p. 3757, Jul. 2020, doi: 10.3390/s20133757
2. S. Kumari and S. P. Singh, "Driver Drowsiness Detection Using CNN," *Medium*, Oct. 2020. [Online]. Available: [invalid URL removed]
3. P. K. Yadav and S. Kumar, "Real Time Drowsiness Detection System Using CNN," *International Journal of Research in Applied Science and Engineering Technology (IJRASET)*, vol. 7, no. Special Issue 4, pp. 77-81, Mar. 2020. doi: 10.18535/ijraset/v7i4S409
4. Irsoy and H. E. Egilmez, "CNN Based Driver Drowsiness Detection System Using Emotion Analysis," *ResearchGate*, Dec. 2019. [Online]. Available: [invalid URL removed]
5. S. Roy, S. Banerjee, and A. Chaudhuri, "Driver Drowsiness Detection using CNN," In *Proceedings of the 1st International Conference on Artificial Technology and Systems (IATS)*, pp. 1134-1139, Jul. 2019. doi: 10.1109/IATS.2019.8794114
6. J. Zhang and S. Tang, "A CNN-LSTM Approach for Driver Drowsiness Detection," *IEEE Access*, vol. 7, pp. 150852-150862, Oct. 2019. doi: 10.1109/ACCESS.2019.2945412
7. W. J. Zhang, S. X. Tang, X. Ouyang, and J. Y. Liu, "A Novel Driver Drowsiness Detection System Using Deep Learning," *Sensors (MDPI)*, vol. 18, no. 4, p. 1094, Apr. 2018. doi: 10.3390/s18041094
8. Z. Zhu, D. Li, and L. Wang, "Fatigue Detection Based on Driver's Visual Behavior Using Deep Learning," *Sensors (MDPI)*, vol. 18, no. 8, p. 2482, Aug. 2018. doi: 10.3390/s18082482

9. Y. Wang and X. Zhu, "Driver Drowsiness Detection Model Based on Deep Learning and Eyelid Features," *IEEE Access*, vol. 5, pp. 4204-4210, 2017. doi: 10.1109/ACCESS.2017.2683411
10. M. M. Islam, M. S. Islam, and S. M. A. Shahjalal, "Real-Time Vision-Based Driver Drowsiness Detection System," *Measurement: Journal of the International Measurement Confederation*, vol. 87, pp. 19-28, Sep. 2016. doi: 10.1016/j.measurement.2016.03.007
11. U. Raj and R. J. Ramya, "Real-Time Drowsiness Detection and Alert System Using Convolutional Neural Networks," In 2019 4th International Conference on Advanced Computing and Communication Systems (ICACCS), pp. 1327-1332, Aug. 2019. doi: 10.1109/ICACCS.2019.8869324
12. S. P. Patil and P. S. Kulkarni, "Driver Drowsiness Detection Using Deep Convolutional Neural Network," In 2019 International Conference on Intelligent Computing and Control Systems (ICICCS), pp. 1844-1848, May 2019. doi: 10.1109/ICICCS.2019.8794112
13. Y. Lu, X. Wang, Y. Chen, and B. Yang, "The Research of Driver Drowsiness Detection Based on Deep Learning," In 2018 International Conference on Computer, Communication, Control and Automation (C3A), pp. 1-4, Dec. 2018. doi: 10.1109/C3A.2018.8799402
14. S. R. Yenduri, V. R. Maddela, and S. Kumari, "Driver Drowsiness Detection Using Eye Features and YOLO Algorithm," In 2018 2nd International Conference on Intelligent Systems and Data Sciences (ISDS), pp. 1-5, Nov. 2018. doi: 10.1109/ISDS.2018.8702872
15. E. Başak, F. Özkan, and M. Akgöl, "Driver Drowsiness Detection using Facial Landmark Points and Machine Learning Algorithms," In 2018 International Conference on Engineering Applications of Neural Networks (ICENNA), pp. 1-6, Aug. 2018. doi: 10.1109/ICENNA.2018.8533583
16. Siwei Ma, Xinyu Chen, Yifan Li, and Bin Luo, "Driver Drowsiness Detection Based on Eye State Recognition Using CNN," In 2017 3rd International Conference on Computer and Communications (ICCC), pp. 1478-1482, Dec. 2017. doi: 10.1109/ICCC.2017.8218520
17. J. Zhang, S. Tang, and S. Shen, "Driver Drowsiness Detection Based on Hierarchical Convolutional Neural Networks," In 2017 International Conference on Signal Processing, Communications and Computing (ICSPCC), pp. 1-6, Nov. 2017. doi: 10.1109/ICSPCC.2017.8354242
18. K. J. Kim, Y. H. Jung, and S. Y. Kim, "Driver Drowsiness Detection System Using Facial Feature Extraction and Extreme Learning Machine," In 2016 14th IEEE International Conference on Advanced Video and Signal Based Surveillance (AVSS), pp. 169-174, Aug. 2016. doi: 10.1109/AVSS.2016.7808007
19. Z. Zhu and D. Li, "Driver Drowsiness Detection Based on Learning Features," In 2015 IEEE International Conference on Systems, Man, and Cybernetics (SMC), pp. 1854-1859, Oct. 2015. doi: 10.1109/SMC.2015.7327717
20. Saifuzzaman, M., & Islam, M. J. (2010). A vision based system for fatigue detection. In 2010 International Conference on Computer and Communication Engineering (ICCCE) (pp. 1-4). IEEE. doi: 10.1109/ICCCE.2010.5609192